



## JENEsys Edge 534 Specifications

- ✓ Powered by Niagara®
- ✓ Supports JAVA Web Start
- ✓ Standard Niagara drivers—Niagara Network (Fox), BACnet, Modbus, Web & oBIX
- ✓ Compatible with many additional 3<sup>rd</sup> party drivers
- ✓ 10 Digital Outputs
  - Form A contacts, 24V at 0.5 Amp
- ✓ 8 Analog Outputs
  - 0-10 Vdc
- ✓ 16 Universal Inputs
  - Type-3 10k ohm thermistors
  - Resistance 0-100 K ohms
  - 0-10 Vdc
  - 0-20 mA using a 499 ohm resistor
  - Pulse input; up to 500Hz
- ✓ 10/100 Mbps Ethernet (2), RS-485 (2), USB (2)
- ✓ Standard RS-485 multi-drop communication bus
- ✓ 4G eMMC flash memory
- ✓ 1GHz AM335x ARM Cortex A-8 Processor
- ✓ Existing Niagara stations can be added
- ✓ 24 Vac/dc power input, ideal for equipment control and monitoring applications
- ✓ Runs on Onyx®—an extensible platform
- ✓ Leverages global capacity licenses
- ✓ 35 mm DIN rail or flat panel mounting

## Deliver the Reliability of Niagara® to the Edge

JENEsys® Edge™ products are a new generation of IoT controllers combining the Niagara Framework® with Lynxspring's Onyx® platform. A first-of-its-kind, the JENEsys Edge 534 is a fully programmable Niagara controller with 34 IO built in and expandable IO available, delivering edge connectivity, interoperability, data access and analytics for today's buildings, energy management, machine-to-machine applications and IoT environments. Taking Niagara to the edge with real-time control—the JENEsys Edge 534 *utilizes the same familiar ProBuilder/Workbench software, Niagara programming tools and Fox Protocol.*

## Connect & Access Data—Anytime, Anywhere

Purpose-built, Lynxspring's JENEsys Edge 534 delivers edge connectivity, data access and control for today's small to mid-sized facilities, plant control, machine-to-machine and IoT applications that require smart edge technology.

## Reduce Engineering Time & Installation Costs

The JENEsys Edge 534 combines Niagara and Onyx, a proven IoT edge hardware platform, enabling facility managers, operators, system integrators and contractors to use a known user interface (*ProBuilder/Workbench*) to achieve operational efficiencies between multiple systems and/or devices, facility management functions, equipment control and business applications. The bottom line is that the JENEsys Edge 534 licensing is *well-suited to take Niagara into smaller or mid-sized and price-sensitive applications.*


## Features

- ✓ JENEsys = fully programmable Niagara controller
  - Fox Protocol
  - Same Programming Tools—ProBuilder/Workbench
- ✓ 34 points of IO on-board and enables an Onyx Network
- ✓ Add to a JENE-EG534, up to 8 additional Onyx XM 34IO extender modules (*at 34 points of IO each*) for a maximum of 306 points
- ✓ Fast & increased memory capacity
- ✓ Small unit footprint (*4.5" x 4.25" x 2.25"*)
- ✓ Real-time Linux OS

# JENEsys<sup>®</sup> Edge<sup>™</sup> 534 – AX

## PRODUCT DATA SHEET

### Dimensions



### Specifications

PLATFORM	
Operating System	Helix <sup>®</sup> Framework by Lynxpring <sup>®</sup> and Niagara <sup>®</sup> AX 3.8.111
Processor	1 GHz AM335x ARM Cortex A8
Memory	512 MB DDR3L 800 MHz, 4 GB 8-bit Embedded MMC on-board Flash
Real-Time Clock (RTC)	Battery-powered clock included to store description/setup values including: year, month, date, hours, minutes and seconds.

COMMUNICATION PORTS	
2 Ethernet Ports	10/100 Mbps ( <i>RJ-45 Connector</i> )
2 RS-485 Ports	Optically-isolated RS-485 serial port with 3-screw connector
Mini-B USB	USB Client Connector utilizes 5-pin Mini-B USB cable
Micro USB	Serial shell access
Onyx Network	3-wire (LxH LxL SHLD) high-speed differential serial signal

INPUTS AND OUTPUTS	
16 Universal Inputs	Type-3 10K ohm thermistors; resistance 0-100K ohms; 0-10 Vdc; 0-20 mA using a 499 ohm resistor; pulse input: up to 500Hz
10 Digital Outputs	Form A contacts, 24V at 0.5 A
8 Analog Outputs	0-10 Vdc
Connector Screw Size	3/32" slotted
Supported Wire Size	28-16 AWG
Housing	UL94V-0

POWER	
Power Input	External 24Vac/dc power supply, minimum 18VA/device

CHASSIS	
Construction	Base: Plastic, DIN rail or screw mount      Cover: Plastic
Cooling	Internal air convection
Dimensions	4.5" (11.43 cm) width x 4.25" (10.8 cm) length x 2.25" (5.72 cm) depth
Mounting	Flat panel and 35mm DIN rail mounting options standard

ENVIRONMENT	
Operating Temperature	0 – 60 °C (32 –140 °F)
Storage Temperature	0 – 70 °C (32 –158 °F)
Relative Humidity Range	5 – 95% RH, non-condensing

CERTIFICATIONS	
Compliance	Approved: FCC 47CFR Parts 15B and 18, EN 55022, EN 55011, ICES-003, RoHS In Process: UL 916, CSA C22.2 No. 205-12, EN 61010-1: 2010, IEC 61010-1, 3rd edition

WEIGHT	
JENE-EG534	0.9 pounds      Product and Packaging      1.6 pounds

### Ordering Information

PART NUMBER(S)	DESCRIPTION
JENE-EG534-100U	Packaging will include one (1) JENEsys-Edge 534 Controller ( <a href="#">LICENSE WITH MAXIMUM OF 100 POINTS, UNLIMITED DEVICES</a> )
JENE-EG534-300U	Packaging will include one (1) JENEsys-Edge 534 Controller ( <a href="#">LICENSE WITH MAXIMUM OF 300 POINTS, UNLIMITED DEVICES</a> )
JENE-PC8000-WPM	Available with power supply option

© 2017 by Lynxpring, Inc. All rights reserved. The information and/or specifications published here are current as of the date of publication of this document. Lynxpring, Inc. reserves the right to change or modify specifications without prior notice. The latest product specifications can be found by contacting our corporate headquarters in Lee's Summit, Missouri. Products or features contained herein are covered by one or more United States or foreign patents. Other brand and product names are trademarks or registered trademarks of their respective holders. This document may be copied by parties who are authorized to distribute Lynxpring products in connection with distribution of those products, subject to the contracts that authorize such distribution. It may not otherwise, in whole or in part, be copied, photocopied, reproduced, translated, or reduced to any electronic medium or machine-readable form without prior written consent from Lynxpring, Inc. Complete Confidentiality, Trademark, Copyright and Patent notifications can be found at: [lynxpring.com/company/legal](http://lynxpring.com/company/legal).

Lynxpring<sup>®</sup>, JENEsys<sup>®</sup>, Onyx<sup>®</sup> and Helix<sup>®</sup> are registered trademarks of Lynxpring, Inc. JENEsys Edge<sup>™</sup> is a trademark of Lynxpring, Inc.  
Niagara Framework<sup>®</sup> is a registered trademark of Tridium, Inc.